



L-sealer with shrink tunnel **KC 8060/650 UNIVERSAL**



Created for demanding industrial applications

Complete product range
for efficient packaging processes

Kallfass 
Results count.

Compact L-sealer with shrink tunnel

KC 8060/650 Universal

The compact L-sealer KC 8060/650 in combination with high performance shrink tunnel. The qualities of this series of machines become evident when subjected to hard, continuous use. Products such as printed material, sets of glassware or oil canisters can all be packed quickly and economically whilst maintaining a high quality.



The figure may show optional equipment, ordered separately

Technical specifications

	KC 8060/650 Universal
Transverse seal bar, length	24
Product clearance height	8
Power supply	208 - 480 Volt
Film, centre-folded film	12 - 80 µm
Transport speed	8 - 39 feet / minute
Packaging capacity, max.	20 cycles / minute



Sovereign and reliable. First L-sealer with PLC SIMATIC S7-1200.

Your benefits highlighted

- Economical packaging of a wide range of products
- Effective and absolutely inodorous mode of operation with proven impulse sealing technology using teflonised sealing and cutting wire
- Electromagnetically operated hooks to apply constant pressure during the sealing cycle
- Accurate maintenance of the set sealing time by PLC SIMATIC S7-1200
- Trouble-free sealing and cutting, even with thicker films through defined contact pressure
- Also with plastic mesh belt available
- T-wire-sealing for thick PE-Film 60µm and upwards

Solution based on Kalfass quality. Competence in production of a wide range of packaging machines, from customer tailored systems to packaging systems for integration into production lines.



KALLFASS is certified according to ISO 9001:2008

www.kalfass-us.com



Complete Packaging Solutions & Systems, Inc.



Results count.