


ENERGY-SAVING SHRINK TUNNEL COMPACT 650 S



Intelligent technology for energy-efficient shrinking

Complete product range for efficient packaging processes





Energy-Saving Shrink Tunnel

COMPACT 650 S

The compact shrink tunnel for small to medium formats. With the extra advantage of heat performance.

The Compact 650 S is ready to go in an instant. It takes just three minutes to heat up. The unique ring-nozzle heating system is easy to install and its intelligent technology is energy efficient.



The figure may show optional equipment, ordered separately

Technical specifications

rechnical specifications	Compact 650 S
Adjustable working height	32 - 35 in.
Tunnel clearance width, height	26 in., 8 in.
Lenght of the heated tunnel hood	48 in.
Power supply	208 - 480 Volt
Continuously adjustable temperature	up to 190°C/375°F
Transport speed	15 - 90 feet / minute
Installed heating capacity	13,5 kW





The ring nozzle heating system provide uniform heat transfer to the packaged product.

Your benefits highlighted

- Perfect packaging results using constantly uniform heat energy transfer to the packaged goods, regardless of the position on the conveyor belt
- Ring nozzle heating technology with integrated air circulating system for efficient energy recovery
- High level of insulation and compact design ensure fast warm-up times
- Easy adjustment of basic parameters (temperature, air volume and package speed) using continuously adjustable controller
- Intelligent technology ensures constant temperature during operation. Energy-intensive temperature fluctuations are prevented
- Carefully selected components, easy to maintain, maintenance-free plastic mesh-belt

Solution with Kallfass quality. Competence in the production of a wide range of products, from individual units to packaging systems to integration into productions lines.



